

Smart Technology
For Security ...

Blue



CV-3W100IPEZ



Support H.264/H.265 Compression
ONVIF 2.4; Support P2P Function
Compatible with Onvif NVR
Intelligent SMD Smart IR
Support Audio (Optional)

Support TF Card (Optional)

Model No.		CV-3W120IPEZ	CV-3W130IPEZ	CV-3W140IPEZ	CV-3W150IPEZ
Sensor		1/2.9" Sony CMOS Sensor Progressive Scan	1/3" CMOS Sensor Progressive Scan	1/3" CMOS Sensor Progressive Scan	1/2.7" Sony CMOS Sensor Progressive Scan
Effective Pixels		1920(H)×1080(V)	2048(H)×1536(V)	2240(H)×1680(V)	2592(H)×1944(V)
Lens		2.5~13.5mm Auto focus Lens			
IR LED		66 Φ 20m Powr IR LED (50-60mtr)			
WDR		WDR>120db			
PoE		Yes			
Network Interface		1 RJ45 Ethernet interface, 10/100M self-adaptive			
Video Compression		H.264 MainProfile		H.265/H.264 MainProfile	
Resolution	Main Stream	Full HD 1080P (1920*1080)25fps	Full HD 1536P (2048*1536)25fps	Full HD 4 MP (2240*1680)25fps	Full HD 5 MP (2592*1944)25fps
	Sub Stream	Q720P(640*360)/VGA(640*480) 25fps			
Video Bitrate		32Kbps-16Mbps continuous adjustable, support CBR/VBRs			
Privacy Mask		4 configurable regions			
Auto Image Control Functions		Auto Exposure Control (AEC); Auto White Balance (AWB); Auto Band Filter (ABF) Auto Black Level Calibration (ABLC)			
Image Controls		Color saturation, hue, gamma, sharpness (edge enhancement), lens correction, defective pixel canceling, and noise canceling			
Communication protocol		TCP/IP、 UDP、 RTP、 RTSP、 RTCP、 HTTP、 DNS、 DDNS、 DHCP、 FTP、 NTP、 PPPOE、 SMTP、 UPNP			
Remote View		Support IE6.0 and above browser(insert Web Server),support 10 visitors in the same time(MAX)			
Mobile Client		Support iPhone、 iPad、 Android			
Environmental Casing		Outdoor Use (IP 66 Rated)			
Operating Temperature		-20 °C ~ 50 °C (-4 °F ~ 122 °F) for DC 12V			
Operating Humidity		0% -85% RH			
Power		DC12V 2.0A/PoE			
Power Consumption		2 W(MAX)	3 W(MAX)		
Dimension		94mmx105mmx323mm			
Weight		1.032kg			
Material		Metal			