

Orange

Smart Technology
For Security ...



CV-CW50IP



5.0 Megapixel 2592 X 1944P (25Fps / 15Fps)
1/2.7" CMOS Sensor Progressive Scan
4 / 6 mm Lens
Support PoE (Optional)

Model No.		CV-CW50IP	
Sensor	1/2.7" CMOS Sensor Progressive Scan		
Effective Pixels	2592(H)x1944(V)		
Lens	4 / 6 mm		
Min.Illumination	Color 0.6Lux@F1.2;white&black0.08Lux@F1.2;		
IR LED	18 Φ 14m SMD IR LED		
IR Distance	20-25 mtrs		
S/N Ratio	≥50db(AGC OFF)		
DWDR	DWDR>80db		
Network Interface	1 RJ45 Ethernet interface, 10/100M self-adaptive		
Video Compression	H.265 / H.264 MainProfile		
Resolution	Main Stream	Full HD 5 MP (2592*1944)25fps	Full HD 5 MP (2592*1944)15fps
	Sub Stream	Q720P(640*360)/VGA(640*480) 25fps	
Video Bitrate	32Kbps-16Mbps continuous adjustable, support CBR/VBRs		
Privacy Mask	4 configurable regions		
Auto Image Control Functions	Auto Exposure Control (AEC); Auto White Balance (AWB); Auto Band Filter (ABF)		
	Auto Black Level Calibration (ABLC)		
Image Controls	Color saturation, hue, gamma, sharpness (edge enhancement), lens correction, defective pixel canceling, and noise canceling		
Communication protocol	TCP/IP、UDP、RTP、RTSP、RTCP、HTTP、DNS、DDNS、DHCP、FTP、NTP、PPPOE、SMTP、UPNP		
Network protocol	Support Onvif 2.4		
Remote View	Support IE6.0 and above browser(insert Web Server),support 10 visitors in the same time(MAX)		
Mobile Client	Support iPhone、iPad、Android		
Environmental Casing	Indoor / Outdoor Use (IP 66 Rated)		
Operating Temperature	-20 °C ~ 50 °C (-4 °F ~ 122 °F) for DC 12V		
Operating Humidity	0% -85% RH		
Power	DC12V 2.0A / PoE		
Power Consumption	3 W(MAX)		
Dimension	183mmx69mmx70mm		
Weight	320g		
Material	Metal		