

Smart Technology
For Security ...

Orange



CV-8224S

H.264 Compression Format

Can connect 24ch 2MP/32ch 1.3MP/32ch 1MP

Powerful mobile control and Powerful CMS feature



Model		NVR-8224S
System	Operating System	Embedded Linux
	System resources	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
Interface	Operator interface	16-bit true color graphic menu operation interface, support mouse operation
	Preview	1/4/8/9/16/24/32
Video	Video input (IP)	24*1080P/32*960P/8*5M/,16,8*1080P/16*720P
	Video standards	PAL(625TVL,50f/s); NTSC(525TVL,60f/s)
	Video compression	H.264
	Display quality	Max 1920*1080
	Playback quality	5M/4M/1080P/960P/720P
	Decode	2*5M/4*4M/4,8,8*1080P/8*960P/16*720P
Audio	Motion detection	Support(depend on camera)
	Audio compression	G.711A
Record & playback	Intercom	Support
	Recording mode	Manual>Alarm>Dynamic Detection>Timing
	Local payback	2*5M/4*4M/4,8,8*1080P/8*960P/16*720P
Storage & Backup	Search mode	Search by Time/Calendar/Event/Channel
	Space occupation	Video: CIF 4~5G/day*channel, D1 8~10G/day*channel; 960H 12G~20G/day*channel 720P 20~30G/day*channel; 1080P ~40G/day*channel; Audio: 691.2M/day*channel
	Record storage	HDD, Network
	Backup mode	Network backup, USB hard disk, USB burner, SATA burner
External interface	Video output	1ch VGA, 1ch HDMI HD Output
	Network interface	1*RJ45 10M/100M/1000M Adaptive Ethernet port
	USB interface	1*USB2.0 ports; 1*USB3.0 ports
	HDD	2 SATA(Up to 6TB for each disk)
General	PTZ control	Control PTZ device by network
	ONVIF	Support
	Power supply	12V/4A
	Power Consumption	<10W(Without HDD)
	Work environment	Temperature:0°C- +55°C, Humidity:10%—90%RH, Atm:86kpa—106kp
	Dimension	325(Length) x 235 (Width) x 52 (Height)