

An ISO 9001-2008 Certified Since: 2005

## Smart Technology For Security



H.265 / H.264 Compression Format
Can connect 4ch 5MP/4ch 4MP/8ch 2MP
Powerful mobile control and powerful CMS Future















	Model	CV-8104SH
System	System resource	Multi-channel real-time recording synchronously, multi-channel real-time playback, multi- channel multi-user network operation, USB back up.
	Operation interface	16 bit real color GUI interface support mouse operation
Display	Display screen	1/4/8 /9screen
	Image encode	H.265(High Profile)
Video	Monitor quality	HDMI : 1080P
	Playback quality	Max support 1080P NVR mode
	Encode capability	4CH*5M/4CH*4M/8CH*2M/4CH*4K
	Decode capability	2CH*5M/4CH*3M/4CH*960P
	Multi-mode video input	NVR mode :8CH*2MP/4CH*5M/4CH*4M/4CH*4K
	Motion detection	Each channel can set 192(16*12)detection area; can set multi-level of flexibility
	Audio compression	G.711A
Audio	Record mode	Manual、alarm、motion detection、timing
	Local playback	1-2ch playback synchronously; Under the mode of NVR, Max support 2CH 1080P playback
Record and	Local playback	synchronously
playback	Video search	Time、date、event、channel search
playback	Space occupation	Video: 1080P 20~30G/day*channel;
	Space occupation	audio: 691.2MB/day*channel
Storage	Video storage	Local HDD 、Network
and back	Back up mode	Network backup、USB portable HDD、USB DVD-RW
up	Video input	8CH 2MP
Interface	Video output	1CH HDMI
	Audio input	NO
	Audio output	NO
	Alarm input	NO
	Alarm output	NO
	Network port	RJ45 10M/100M self-adaptive Ethernet port
	PTZ control	1 RS485; support multi kinds of PTZ Protocol
	USB port	2*USB2.0
	HDD port	1 SATA(max 6TB)
	Wireless port	3G、WIFI(extension via USB port)
	Tour	Yes
other	Remote controller	No
	Power	12V/4A
	Dimension	260(Length) x 234(Width) x 47(Height)