

Specification	Model No:CV-9216AHD
Operating System	Embedded Linux
DVR Mode	Support, Max 16ch AHD@1080P/960P/720P;
Mixed Mode	Support, Max 16CH
NVR Mode	Max 16 CH IPCAM video real time input
IP video input	Max 16 CH 1080P, RJ45 interface
Protocol	ONVIF,N1
IPC Remote Setting	Time synchronization setting/ encoding setting color adjust/ Motion detection/ PTZ
Video input format	TVI 2.0 720P@25/30/50/60fps,1080P@25/30fps, AHD 720P@25/30fps,1080P@25/30fps, CVBS 960H@PAL/NTSC
Video encoding resolution	1080P-H(960x1080)/720P@16fps; 960H/D1@25fps
Video encoding rate	512 Kbps -- 4Mbps
UTC	Support 8ch
Audio input	Support 2ch
Audio encoding	G.711
HDMI output	1 CH HDMI Interface ; Max Resolution : 1920x1080/60Hz
VGA output	1 CH VGA Interface ; Max Resolution : 1920x1080/60Hz
Audio output	RCA Audio output *1, HDMI Audio output
Stream type	Audio and video flow mixing flow/video stream
Video Compression	H.264
Audio Compression	G.711
Recording	DVR mode : 16 CH 720P/Half-1080P Recording Mixed mode or NVR mode : 16 CH 1080P Recording
Playback	DVR mode : 4 CH 720P/Half-1080P Playback Mixed mode or NVR mode : 4
Recording Mode	Manual, Schelude (Reguler/Continuous), MD,Alarm, Stop
Search Mode	Time/Date, Alarm, MD &Exact Search (accurate & Second), Smart Search
Trigger Events	Recording, PTZ,Tour,Alarm, Video Push,Email,Buzzer, Snapshot On Email
Device Control	Remote Control & Mouse
Soft Power-Off	Support
Storage Type	2 * SATA Interface
Storage Capacity	6TB In Max
Backup	USB Backup & Internet Backup
Network Interface	RJ45 10M / 100M Internet Interface
USB Interface	2 * USB2.0 Interface
Serial Interface	1 * RS485 Interface
Power	DC +12 V / 3.4A (6A@4*SATA)
Power Consumption	<20W
Working humidity	10%--90%
Weight Net	1.860KG
Weight Gross	2.960KG





