

Specification	Model No:CV-9408AHD
Operating System	Embedded Linux
Video Compression	H.264
DVR Mode	Support, Max 8ch AHD@4MP/3MP/1080P/960P/720P; TVI@4MP/3MP/1080P/960P/720P; CVI@1080P/720P; IPC@3MP/1080P/720P;analog video real time input
Mixed Mode	Support, Max 8 ch, Arbitrary proportion analog channels and IPCAM channel
NVR Mode	Max 8ch IPCAM video real time input
IP video input	Max 8 ch 3MP, RJ45 interface
Protocol	ONVIF,N1
IPC Remote Setting	Time synchronization setting/ encoding setting color adjust/ Motion detection/ PTZ
Video input format	AHD (720P@25/30fps,1080P@25/30fps,3MP@18fps,4MP@15fp s/25fps/30fps),
Video encoding resolution	4MP-H(1280*1440)@15fps 3MP(1920*1536)@12fps 1080P@15fps
Video encoding rate	512 Kbps -- 4Mbps
UTC	Support 8ch
Audio input	Support 2ch
HDMI output	1 CH HDMI Interface ; Max
VGA output	1 CH VGA Interface ; Max Resolution : 1920x1080/60Hz
Audio output	RCA Audio output *1, HDMI Audio output
Stream type	Audio and video flow mixing flow/video stream
Audio Compression	G.711
Recording	DVR mode : 8 CH 720P/Half-1080P/1080P/3.0MP
Playback	3mp camera:2CH 1080P Playback, 2 CH 4MP-H/ Playback , 1CH 3MP Playback without 3mp camera: 4ch 1080P/4MP-H playback
Recording Mode	Manual, Schelude (Reguler/Continuous), MD,Alarm, Stop
Search Mode	Time/Date, Alarm, MD &Exact Search (accurate & Second), Smart Search
Trigger Events	Recording, PTZ,Tour,Alarm, Video Push,Email,Buzzer, Snapshot Snapshot On Email
Device Control	Remote Control & Mouse
Soft Power-Off	Support
Storage Type	2* SATA Interface
Storage Capacity	6TB In Max
Backup	USB Backup & Internet Backup
Network Interface	RJ45 10M / 100M Internet Interface
USB Interface	2 * USB2.0 Interface
Serial Interface	1 * RS485 Interface
Power	DC +12 V / 3.5A (4A@2*SATA)
Power Consumption	<10W
Working humidity	10%--90%
Dimension	320*250*48

Weight Net	0.740KG
Weight Gross	1.340KG

