

Specification	Model No:CV-9416AHD
Operating System	Embedded Linux
Video Compression	H.264
DVR Mode	Support, Max 16ch AHD@4MP/3MP/1080P/960P/720P; TVI@4MP/3MP/1080P/960P/720P;
Mixed Mode	Support, Max 16 ch, Arbitrary proportion analog channels and IPCAM channel
NVR Mode	Max 16ch IPCAM video real time input
IP video input	Max 16 ch 3MP, RJ45 interface
Protocol	ONVIF,N1
IPC Remote Setting	Time synchronization setting/ encoding setting
Video input format	AHD (720P@25/30fps,1080P@25/30fps, 3MP@18fps,4MP@15fps/25fps/30fps, TVI2.0 (720P@25/30/50/60fps,1080P@25/30fps,3MP@1
Video encoding resolution	4MP-H(1280*1440)@15fps 3MP(1920*1536)@12fps 1080P@15fps
Video encoding rate	512 Kbps -- 4Mbps
UTC	Support 16ch
Audio input	Support 16ch
HDMI output	Max Resolution : 4K/30Hz
VGA output	1 CH VGA Interface ; Max
Audio output	RCA Audio output *1, HDMI Audio output
Stream type	Audio and video flow mixing flow/video stream
Audio Compression	G.711
Recording	DVR mode : 8 CH 720P/Half-1080P/1080P/3.0MP
Playback	4CH 4MP-H/4CH 3MP/4Ch 1080P/4CH 720Pplayback
Recording Mode	Manual, Schelude (Reguler/Continuous), MD,Alarm, Stop
Search Mode	Time/Date, Alarm, MD &Exact Search (accurate & Second), Smart Search
Trigger Events	Recording, PTZ,Tour,Alarm, Video Push,Email,Buzzer, Snapshot Snapshot On Email
Device Control	Remote Control & Mouse
Soft Power-Off	Support
Storage Type	2* SATA Interface
Storage Capacity	6TB In Max
Backup	USB Backup & Internet Backup
Network Interface	RJ45 10M / 100M Internet Interface
USB Interface	2 * USB2.0 Interface
Serial Interface	1 * RS485 Interface
Power	DC +12 V / 3.5A (4A@2*SATA)
Power Consumption	<10W
Working humidity	10%--90%
Working humidity	10%--90%
Dimension	250(L)x210(W)x45(H)mm
Net Weight	1.22kg±1.60kg

Weight Gross

1.340KG

