

Specification	Model No:CV-CW40AHD
Image Sensor	1/3" CMOS Sensor
Pixels	PAL:2688H×1520V NTSC: 2688H×1520V
System	PAL/NTSC
Resolution	4MP
Shutter	Auto / Manual 1/25 (1/30) seconds to 1 / 50,000 sec
AGC	AGC/ AGC + Slow Shutter
SYNC	INNER SYNC
S/N Ratio	>50dB(AGC OFF)
Video output	1.0Vp-p,75Ω
IR LED	18 SMD LED
IR Range	30 Meters
Minimum	Color 0.5Lux (F1.2,50IRE,AGC ON), B/W:0.01Lux (F1.2,50IRE,AGC ON)
Lens	3.6MM IP Lens
D/N Switch	Color /Auto
D/N Switch time	0~255
Lens style	Manual/Auto
Privacy Zones	1~15zones
Motion Detect	4 Zones
Video output	BNC
White Balance	ATW /PUSH/User1/ User 2/ Manual/ ANTI CR/PUSH LOCK
Mirror	Vertical/ Horizontal / Vertical + Horizontal /Off
Title	Can be Set
Title Position	Any Position on the Screen
DNR	High/Medium to high/Medium
OSD	Optional
Pic sharpness	0-15
Power	DC12V±10% (AC24V optional)
Power Consumption	3.792 Watt (After IR LED Powered ON)
Wattage	5.0W
Operating Temperature	-10°C~ 50°C
Operating Humidity	<90%
Storage Temperature	-40°C~+60°C
Storage Humidity	20~95%
Dimension	220(W)*70(H)
Housing type	Metal (IP66) Housing
Weight Net	0.280KG
Weight Gross	0.400KG

